



**TECHNICAL SPECIFICATION**

<b>Section</b>	Triangular 40 cm long sides
<b>Material</b>	Aluminium EN AW 6082 T6
<b>Ends</b>	Aluminium casting plate EN AB-44100
<b>Connection</b>	SSF03 – KB6
<b>Weight</b>	6.00 kg
<b>Welding</b>	TIG UNI EN 9606-2:2006
<b>Main tubes</b>	Ø 50x2 mm
<b>Diagonals</b>	Ø 20x2 mm

**INERTIAL PROPERTIES**

<b>Area / Area</b>	(A)	9.03	cm <sup>2</sup>
<b>Modulo Elastico / elastic modulus</b>	(E)	700.000	Kg / cm <sup>2</sup>
<b>Momento d'inerzia / moment of inertia</b>	(I <sub>y</sub> )	1958	cm <sup>4</sup>
<b>Momento d'inerzia / moment of inertia</b>	(I <sub>x</sub> )	1873	cm <sup>4</sup>
<b>Modulo Di resistenza elastico / elastic moment resistance</b>	(W <sub>y</sub> )	120	cm <sup>3</sup>
<b>Modulo Di resistenza elastico / elastic moment resistance</b>	(W <sub>x</sub> )	110	cm <sup>3</sup>